



**PROPSPEED ETCHING PRIMER BASE**  
Safety Data Sheet

**Section 1 - Identification of the Material and the Supplier**

**1.1 Product identifier**

<b>Product name</b>	Propspeed Etching Primer Base
<b>Product code</b>	Component in Propspeed kits: 782A(1L), 783A (500ml), 783kit (200mL),and Etching Hardener kit (782BC).

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

<b>Identified uses</b>	Metal Primer Base (Part A)
<b>Restrictions of use</b>	Refer to Section 15

**1.3 Details of the supplier of the Safety Data Sheet**

<b>Supplier</b>	Propspeed International Ltd PO Box 83232 Edmonton Auckland New Zealand <a href="http://www.propspeed.com">www.propspeed.com</a>
-----------------	--

<b>Telephone</b>	+64 9 524 1470
<b>Telefax</b>	+64 9 813 5246

**E-mail (competent person)** info@propspeed.com

**1.4 Emergency telephone number**

<b>Emergency number</b>	New Zealand	0800 243 622
(24h/24 – 365 d/year)	Australian	1800 127 406
	Global Access	+ 64 4 917 988

**NZ National Poisons Centre Telephone** +64 4 917 9888 (ChemCall)

## Section 2 - Hazards identification

**Hazardous Status:** This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

**EPA Approval Code:** Surface Coatings and Colourants (Flammable, Corrosive, Toxic [6.7]) – HSR002664

### GHS pictograms:



GHS Signal word: **Danger**

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1B	H225	Highly flammable liquid and vapour.	Flam. Liq. 2
6.1E (oral)	H303	May be harmful if swallowed.	Acute Tox. 5
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.6A	H340	May cause genetic defects.	Muta. 1A
6.7A	H350	May cause cancer.	Carc. 1A
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
8.2C	H314	Causes severe skin burns and eye damage.	Skin Corr. 1C
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.

# PROPSPEED ETCHING PRIMER BASE

## Safety Data Sheet

P241	Use explosion-proof electrical, ventilation and lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes, vapours and spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing in Section 8.
P281	Use personal protective equipment as required.

<b>Response Code</b>	<b>Response Statement</b>
P101	If medical advice is needed, have product container or label at hand.
P310	Immediately call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use AFFF alcohol compatible foam or water spray for extinction.

<b>Storage Code</b>	<b>Storage Statement</b>
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

<b>Disposal Code</b>	<b>Disposal Statement</b>
P501	Dispose of according to local regulations

**Section 3 - Composition/information on ingredients****Hazard Component**

<b>Ingredient name</b>	<b>CAS No.</b>	<b>Content Weight%</b>
Propan-2-ol	30-60	67-63-0
2-Methylpropan-1-ol	10-30	78-83-1
Zinc chromate	5-10	13530-65-9
Xylene	5-10	1330-20-7
Talc	1-5	14807-96-6
Non-hazardous ingredients	To balance	

**Section 4 - First aid measures**

Burns	Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.
If in Eyes	Immediately flush with plenty of water. Remove any contact lenses and open eyes wide apart. Call an ambulance and continue flushing during transportation to hospital. Bring these instructions.
If on Skin	Remove contaminated clothing immediately and wash skin with soap and water. Important to remove the substance from the skin immediately. Continue to rinse for at least 15 minutes and seek medical attention.
If Swallowed	Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician immediately.
If Inhaled	Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if needed.

**Most important symptoms and effects, both acute and delayed**Symptoms

Ingestion:	May be harmful if swallowed.
Inhalation:	Not applicable
Skin:	Causes severe skin burns and eye damage. May cause an allergic skin reaction.
Eye:	Causes serious eye irritation.
Chronic:	May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### Section 5 – Firefighting measures

<b>Hazard Type</b>	Flammable liquid
<b>Hazards from decomposition products</b>	None in particular
<b>Suitable Extinguishing media</b>	Extinguish with carbon dioxide or dry powder.
<b>Precautions for firefighters and special protective clothing</b>	Selection of respiratory protection for fire- fighting: follow the general fire precautions indicated in the workplace.
<b>HAZCHEM CODE</b>	3YE

### Section 6 - Accidental release measures

Avoid any exposure. Do not smoke, use open fire or other sources of ignition. For personal protection, see section 8. Follow precautions for safe handling described in this safety data sheet.

Absorb spillage with non-combustible, absorbent material. Do not use sawdust or other combustible material. Collect spillage in metal/plastic container with tight-fitting lid, with indication of the contents.

### Section 7 - Handling and storage

#### Precautions for safe handling:

- Keep out of reach of children.
- Read label before use.
- Read safety data sheet before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Keep container tightly closed.
- Use only non-sparking tools.
- Use explosion proof electrical equipment, ventilation and lighting
- Take precautionary measures against static discharge.
- Avoid breathing fumes and vapours or sprays.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing and protective equipment.

**Conditions for safe storage:**

- Store in a flameproof, well-ventilated area.
- Electrostatic charges may be generated during transfer of product from its container.
- Ensure that all equipment is electrically earthed.
- Keep container closed and store away from water or moisture.
- Vapours may form explosive mixtures with air.
- Do not store with oxidizing agents.
- Store locked up.

**Section 8 - Exposure controls/personal protection**

**WORKPLACE EXPOSURE STANDARDS** (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg.m <sup>3</sup>	ppm	mg.m <sup>3</sup>
Propan-2-ol	400	983	500	1250
2-Methylpropan-1-ol	50	152		
Xylene, o-, m-, p-or mixed Isomers	50	217		
Talc, respirable dust		2		
Zinc chromates, as Cr 6.7A [13530-65-9]		0.01		

*NZ Workplace Exposure Standard and Biological Exposure Indices - Nov 2017. The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.*

**Engineering Controls:**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. An eye wash bottle must be available at the work site. Mix and prepare in a place with efficient exhaust ventilation.

**Personal Protection Equipment**



Respiratory	In case of inadequate ventilation, use air-supplied full-mask.
Hands	Wear protective gloves. Nitrile gloves are recommended, but be aware that the

# PROPSPEED ETCHING PRIMER BASE

## Safety Data Sheet

	liquid may penetrate the gloves. Frequent change is advisable. Other types of gloves can be recommended by the glove supplier.
Eyes	Tight fitting safety goggles or face shield should be used. Avoid wearing contact lenses.
Skin	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene	Wash hands after handling. When using do not eat, drink or smoke. Personal protection may not be worn during meal breaks. Personal protection must be kept separate from other clothes. Do not store tobacco, food or beverage in work rooms or areas where the product is used. Contaminated clothing to be placed in closed container until disposal or decontamination. Warn cleaning personnel of chemical's hazardous properties.

### Section 9 – Physical and chemical properties

Appearance	liquid paint
Colour	yellow
Odour	solvent
Odour threshold	data not available
pH	not applicable (solvent based product)
Boiling point	81 – 108°C
Melting point	data not available
Freezing point	data not available
Flash point	14°C
Flammability	data not available
Upper and lower Explosive Limits	1.1 – 12.0 vol %
Vapour pressure	4266 Pa
Relative vapour density	~ 2.1 (air=1)
Specific gravity	0.87 – 0.92 g.cm <sup>-3</sup>
Water solubility	Insoluble in water, soluble in organic solvents
Partition coefficient	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	500 – 750cP
Particle Characteristics	data not available

**Section 10 – Stability and reactivity**

<b>Stability of Substance</b>	Stable under normal usage conditions. Curing time: 10 min - 1 h (20°C)
<b>Possibility of hazardous reactions</b>	Not Available
<b>Conditions to Avoid</b>	Avoid heat, flames and other sources of ignition.
<b>Incompatible Materials</b>	Avoid contact with alkalis. Avoid contact with oxidisers or reducing agents.
<b>Hazardous Decomposition Products</b>	None in particular.

**Section 11 – Toxicological information**

**Acute Effects:**

Swallowed	May be harmful if swallowed.
Dermal	May be harmful if in contact with skin.
Inhalation	Not applicable.
Eye	Causes serious eye irritation.
Skin	Causes severe skin burns and eye damage. May cause an allergic skin reaction.

**Chronic Effects:**

Carcinogenicity	May cause cancer.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell Mutagenicity	May cause genetic defects.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

**Ingredient Data**

**Acute Oral Toxicity**

Propan-2-ol	LD50(mouse)	= 3600 mg/kg
2-Methylpropan-1-ol	LD50 (rat)	= 2460 mg/kg
Xylene	LD50 (mouse)	= 1590 mg/kg

**Acute Dermal Toxicity**

2-Methylpropan-1-ol	LC50 (rat)	= 3400 mg/kg
---------------------	------------	--------------



**Inhalation**

Xylene LC50 (mouse) = 27.6 mg/L

**Special Effects:**

Contains: Zinc chromate

Carcinogen Category 1. Known or suspected carcinogen for humans.

May cause sensitisation.

**Section 12 – Ecotoxicological information**

HSNO Classifications: 9.1B = Toxic to aquatic life with long lasting effects.  
Zinc chromate: L(E)C50 > 0.1 ≤ 1 mg/l

**Environmental Precautions**

Persistence and Degradability The product hardens to a not readily degradable mass. This product is expected to be not readily biodegradable.

Bioaccumulation: No data available

Mobility in Soil The product hardens to a solid immobile substance. The product contains substances, which are water soluble and may spread in water systems. The product contains volatile substances, which may spread in the atmosphere.

Other adverse effects No data available

**Section 13 – Disposal considerations**

**Disposal Method:**

Spent media that has removed toxic chemicals should be examined for specific hazards. Dispose of according to Local Regulations.




Ensure any container holding waste product or contaminated spill media is labelled “Hazardous Waste – Flammable” and that the label also has the Flammable Pictogram, waste type identifier, and the business name, address, and phone number.

**Precautions or methods to avoid:** Avoid release to the environment.

**PROPSPEED ETCHING PRIMER BASE**  
Safety Data Sheet

**Section 14 – Transport information**

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012

	Road and Rail	Marine Transport (IMDG)	Air Transport (IATA)
<b>UN number</b>	1263	1263	1263
<b>UN proper shipping name</b>	PAINT	PAINT	PAINT
<b>Transport hazard class(es)</b>	3 	3 	3 
<b>Packing group</b>	II	II	II
<b>Hazchem</b>	3YE	3YE	3YE
<b>Marine Pollutant</b>		Yes	
<b>EmS</b>		F-E, S-E	

**Limited Quantities Statement:**

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

**Section 15 – Regulatory information**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Corrosive, Toxic [6.7]) – HSR002664

HSNO Classes: 3.1B, 6.1E (oral), 6.4A, 6.5B, 6.6A, 6.7A, 6.8B, 6.9B, 8.2C, 9.1B.

**HSNO Controls**

Trigger quantities for this substance:

<b>HSW (HS) Regulations 2017 and EPA Notices</b>	<b>Trigger Quantity</b>
Certified Handler	Not required
Location Certificate	100L(>5L), 250L (<5L), 50L open (3.1B)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L(3.1B)
Emergency Response Plan	1000L(3.1B)

# PROPSPEED ETCHING PRIMER BASE

## Safety Data Sheet

Secondary Containment	1000L(3.1B)
Fire Extinguishers	At least 2 x 4.5kg powder extinguishers required when 250L is present in a workplace.
Restriction of Use	Only use for the intended purpose.

### Section 16 – Other information

#### Glossary

EC50	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms
HSW	Health and Safety at Work.
LC50	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD50	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
STOT/SE	Specific target organ toxicity – single exposure
STOT/RE	Specific target organ toxicity – repeated exposure
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

#### Reference:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Issue Date: 1 August 2018

Review Date: 1 August 2023

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS. The information herein is given in good faith, but no warranty, express or implied is made. Please contact the New Zealand distributor, if further information is required.